



**25G COMPACT TOOL CARRIER**

**Engine**

Make and Model Kohler Command Pro  
 Power 25 hp (18.6 kW)  
 Cooling system Air  
 Fuel Type Gasoline

**Drive System**

Wheeled

**Performance**

**50% Tip Capacity**  
 Operating Capacity\* 500lb.(215 kg)  
 Tipping Load 1005lb.(431 kg)  
 Break Out Force 1450 lb. (658 kg)  
 Travel Speed-High 3 mph (4.8km/hr.)  
 Travel Speed- Low 1.2 mph (1.9 km/hr.)

**Hydraulics**

Hydraulic Flow, High 8.5 gpm (32.2 l/m)  
 Hydraulic Flow, Low 3.0 gpm (11.4 l/m)  
 System Relief Pressure 3000 psi (207 bar)

**Fluid Capacities**

Fuel Tank 3.2 gal (12.1l)  
 Oil Tank 11.6 gal (44 l)

**Dimensions and Weight**

Length (less bucket) 61.3 in (1556 mm)  
 Width (less bucket) 39.9 in (1013 mm)  
 Height to Hinge Pin 68.3 in (1734 mm)  
 Ground Clearance 4.3 in (108 mm)  
 Operating Weight 1770lbs. (803 kg)

**Standard Features**

Hydraulic Controls Lockout  
 Traction Drive Lockout  
 Aux Circuit Equipped with Cylinder Spool  
 Aux Circuit Equipped with Motor Spool  
 Hydraulic Oil Cooler w/ auto Fan  
 Shielded Aux Hydraulic Hoses  
 Single Lever Joystick Hydraulic Control  
 Single Hand Steering  
 Bucket Self-Leveling System  
 Boom Support  
 Parking Brake  
 Universal Q-Tach Frame  
 Lifting Lugs  
 Transportation Tie Downs  
 Padded Operator Area  
 12 Volt Accessory Plug  
 18 x 8.50-8 tires  
 Work light  
 Boosting Lug  
 Operator Platform  
 Dual Lift Cylinders  
 Dual Lift Arm

Cat. No.	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP Euro	MSRP GBP
U-2871	ML25G Loader Base Machine only	1,520 lbs. (689 kg)	15,998	15,998	12,901	10,387
U-2728	Standard 42" Bucket (1067 mm)	120 lbs. (54)	508.00	508.00	409.68	329.87

\* Tipping load based on 200 lb. operator

\* Prices are Ex works Woodstock NB, Canada and subject to change without notice



**25GT COMPACT TOOL CARRIER**

**Engine**

Make and Model Kohler Command Pro  
 Power 25 hp (18.6 kW)  
 Cooling system Air  
 Fuel Type Gasoline

**Drive System**

Track

**Performance**

	<b>50% Tip Capacity</b>	<b>35% Tip Capacity</b>
Operating Capacity*	555lb.(252 kg)	390 lb. (177 kg)
Tipping Load	1113lb.(505 kg)	
Break Out Force	1680lb. (658 kg)	
Travel Speed-High	3.2mph (5.1km/hr.)	
Travel Speed- Low	1.5 mph (2.4 km)	

**Hydraulics**

Hydraulic Flow, High 8.5 gpm (32.2 l/m)  
 Hydraulic Flow, Low 3.0 gpm (11.4 l/m)  
 System Relief Pressure 3000 psi (207 bar)

**Fluid Capacities**

Fuel Tank 3.2 gal (12.1l)  
 Oil Tank 11.6 gal (44 l)

**Dimensions and Weight**

Length (less bucket) 61.3 in (1556 mm)  
 Width (less bucket) 42.3 in (1074 mm)  
 Height to Hinge Pin 69.3 in (1760 mm)  
 Ground Clearance 6.6 in (168 mm)  
 Operating Weight 2220 lbs. (1007 kg)

**Standard Features**

Hydraulic Controls Lockout  
 Traction Drive Lockout  
 Aux Circuit Equipped with Cylinder Spool  
 Aux Circuit Equipped with Motor Spool  
 Hydraulic Oil Cooler w/ auto Fan  
 Shielded Aux Hydraulic Hoses  
 Single Lever Joystick Hydraulic Control  
 Single Hand Steering  
 Bucket Self-Leveling System  
 Boom Support  
 Parking Brake  
 Universal Q-Tach Frame  
 Lifting Lugs  
 Transportation Tie Downs  
 Padded Operator Area  
 12 Volt Accessory Plug  
 230 mm (9") track  
 Work light standard  
 Boosting Lug  
 Operator Platform  
 Dual Lift Cylinders  
 Dual Lift Arm

Cat. No.	Description	Shipping Weight	MSRP	MSRP	MSRP	MSRP
			CDN	US	Euro	GBP
U-3896	ML25GT Loader Base Machine only	1,920 lbs. (871 kg)	18,627	18,627	15,021	12,095
U-2728	Standard 42" Bucket (1067 mm)	120 lbs. (54)	508.00	508.00	409.68	329.87

\* Tipping load based on 200 lb. operator

\* Prices are Ex works Woodstock NB, Canada and subject to change without notice



Price List – June 1, 2012

**35DW COMPACT TOOL CARRIER**

**Engine**

Make and Model Kubota D1105  
 Power 24.8 hp (18.5kW)  
 Cooling system Liquid  
 Fuel Type Diesel

**Drive System** Wheeled

**Performance**

**50% Tip Capacity**  
 Operating Capacity 565lb.(257 kg)  
 Tipping Load 1135 lb.(515 kg)  
 Break Out Force 2090lb. (703 kg)  
 High Speed 2.9 mph (4.6km/hr.)  
 Low Speed 2 mph (3.1 km/hr.)  
 Inching Speed 0.4 mph (0.6 km/hr.)  
 Travel Speed 3.6 mph (5.8 km/hr.)

**Hydraulics**

Hydraulic Flow, High 8.5 gpm (32.1 l/m)  
 Hydraulic Flow, Low 5.5 gpm (20.8 l/m)  
 Combined Flow 14 gpm (53.0 l/m)  
 System Relief Pressure 3000 psi (207 bar)

**Fluid Capacities**

Fuel Tank 10 gal (38l)  
 Oil Tank 11gal (41.6 l)

**Dimensions and Weight**

Length (less bucket) 63.3 in (1607 mm)  
 Width (less bucket) 41.0 in (1041 mm)  
 Height to Hinge Pin 67.8 in (1722 mm)  
 Ground Clearance 5.0 in (127 mm)  
 Operating Weight 2100lbs. (953 kg)

**Standard Features**

Hydraulic Controls Lockout  
 Traction Drive Lockout  
 Aux Circuit Equipped with Cylinder Spool  
 Aux Circuit Equipped with Motor Spool  
 Hydraulic Oil Cooler w/ auto Fan  
 Shielded Aux Hydraulic Hoses  
 Single Lever Joystick Hydraulic Control  
 Single Hand Steering  
 Bucket Self- Leveling System  
 Boom Support  
 Parking Brake  
 Self-Leveling bucket support system  
 Universal Q-Tach Frame  
 Lifting Lugs  
 Transportation Tie Downs  
 Dual Lift Arm Design  
 Padded Operator Area  
 12 Volt Accessory Plug  
 18 x 8.50-8 tires  
 Work light standard  
 Combiner Valve  
 Boosting Lug  
 Operator Platform

Cat. No.	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP Euro	MSRP GBP
U-3897	35DW Loader Base Machine only	1,800 lb (816 kg)	21,399	21,399	17,256	13,895
U-2728	Standard 42" Bucket (1067 mm)	120 lbs. (54kg)	508.00	508.00	409.68	329.87

\*Tipping load based on 200 lb. operator

\* Prices are Ex works Woodstock NB, Canada and subject to change without notice

Provisional Specifications June 2012

1-866-Be-Tough (866-238-6844)



Price List – June 1, 2012

## 35DTN COMPACT TOOL CARRIER

### Engine

Make and Model Kubota D1105  
 Power 24.8 hp (18.5kW)  
 Cooling system Liquid  
 Fuel Type Diesel

### Drive System

Track

### Performance

	50% Tip Capacity	35%Tip Capacity
Operating Capacity	590lb.(249 kg)	415 lb. (190kg)
Tipping Load *	1180lb.(535 kg)	
Break Out Force	2090lb. (703 kg)	
High Speed	3.2 mph (5.2km/hr.)	
Low Speed	2.2 mph (3.5 km/hr.)	
Inching Speed	0.4 mph (0.6 km/hr.)	
Travel Speed	4.1 mph (6.5 km/ hr.)	

### Hydraulics

Hydraulic Flow, High 8.5 gpm (32.1 l/m)  
 Hydraulic Flow, Low 5.5 gpm (20.8 l/m)  
 Combined Flow 14 gpm (52.9 l/m)  
 System Relief Pressure 3000 psi (207 bar)

### Fluid Capacities

Fuel Tank 10 gal (38 l)  
 Oil Tank 11 gal (41.6 l)

### Dimensions and Weight

Length (less bucket) 63.3 in (1607 mm)  
 Width (less bucket) 35.6 in (905 mm)  
 Height to Hinge Pin 68.8 in (1746 mm)  
 Ground Clearance 6.0 in (152 mm)  
 Operating Weight 2450 lbs. (1111 kg)

### Standard Features

Hydraulic Controls Lockout  
 Traction Drive Lockout  
 Aux Circuit Equipped with Cylinder Spool  
 Aux Circuit Equipped with Motor Spool  
 Hydraulic Oil Cooler w/ auto Fan  
 Shielded Aux Hydraulic Hoses  
 Single Lever Joystick Hydraulic Control  
 Single Hand Steering  
 Bucket Self-Leveling System  
 Boom Support  
 Parking Brake  
 Universal Q-Tach Frame  
 Lifting Lugs  
 Transportation Tie Downs  
 Padded Operator Area  
 12 Volt Accessory Plug  
 180 mm (7.09”) wide tracks  
 Work light standard  
 Combiner Valve  
 Boosting Lug  
 Operator Platform  
 Dual Lift Cylinders  
 Dual Lift Arm Design

Cat. No.	Description	Shipping Weight	MSRP CDN	MRP US	MRP Euro	MRP GBP
U-3899	35DTN Loader Base Machine only	2,150 lbs.(975 kg)	23,687	23,687	19,102	15,381
U-2728	Standard 42” Bucket (1067mm)	120 lbs. (54 kg)	508.00	508.00	409.68	329.87

\* Tipping load based on 200 lb. operator

\* Prices are Ex works Woodstock NB, Canada and subject to change without notice

Provisional Specifications June 2012

1-866-Be-Tough (866-238-6844)



Price List – June 1, 2012

**35DT COMPACT TOOL CARRIER**

**Engine**

Make and Model Kubota D1105  
 Power 24.8 hp (18.5kW)  
 Cooling system Liquid  
 Fuel Type Diesel

**Drive System**

Track

**Performance**

	<b>50% Tip Capacity</b>	<b>35%Tip Capacity</b>
Operating Capacity*	620lb.(249 kg)	430 lb. (190kg)
Tipping Load	1235 lb.(499 kg)	
Break Out Force	2090lb. (703 kg)	
High Speed	3.2 mph (5.2km/hr.)	
Low Speed	2.2 mph (3.5 km/hr.)	
Inching Speed	0.4 mph (0.6 km/hr.)	
Travel Speed	4.1 mph (6.5 km/hr.)	

**Hydraulics**

Hydraulic Flow, High 8.5 gpm (32.1 l/m)  
 Hydraulic Flow, Low 5.5 gpm (20.8 l/m)  
 Combined Flow 14 gpm (52.9 l/m)  
 System Relief Pressure 3000 psi (207 bar)

**Fluid Capacities**

Fuel Tank 10 gal (38l)  
 Oil Tank 11gal (41.6 l)

**Dimensions and Weight**

Length (less bucket) 63.3 in (1607 mm)  
 Width (less bucket) 41.5 in (905 mm)  
 Height to Hinge Pin 68.8 in (1746 mm)  
 Ground Clearance 6.0 in (152 mm)  
 Operating Weight 2500lbs. (1134 kg)

**Standard Features**

Hydraulic Controls Lockout  
 Traction Drive Lockout  
 Aux Circuit Equipped with Cylinder Spool  
 Aux Circuit Equipped with Motor Spool  
 Hydraulic Oil Cooler w/ auto Fan  
 Shielded Aux Hydraulic Hoses  
 Single Lever Joystick Hydraulic Control  
 Single Hand Steering  
 Bucket Self-Leveling System  
 Boom Support  
 Parking Brake  
 Universal Q-Tach Frame  
 Lifting Lugs  
 Transportation Tie Downs  
 Padded Operator Area  
 12 Volt Accessory Plug  
 230mm (9.06") wide tracks  
 Work light standard  
 Combiner Valve  
 Boosting Lug  
 Operator Platform  
 Dual Lift Cylinders  
 Dual Lift Arm Design

Cat. No.	Description	Shipping Weight	MSRPC DN	MSRP US	MSRP Euro	MSRP GBP
U-3898	35DT Loader Base Machine only	2,200 lbs.(998 kg)	23,999	23,999	19,354	15,583
U-2728	Standard Bucket width 42" (1067 mm)	120 lbs. (54kg)	508.00	508.00	409.68	329.87

\*Tipping load based on 200 lb. operator

\* Prices are Ex works Woodstock NB, Canada and subject to change without notice

Provisional Specifications June 2012

1-866-Be-Tough (866-238-6844)

<b>Bucket</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
U-2728	Standard Bucket SAE heaped capacity 4.7 cu ft (.13 cu m)	120 lbs (54 kg)	\$ 508.00	\$ 508.00	€ 409.68	£ 329.87

<b>AUGER</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
U-2776	Post Hole Auger less bit	150 lbs (68 kg)	\$ 2,162.00	\$ 2,162.00	€ 1,743.55	£ 1,403.90
U-2779	6" x 3" Bit	32lbs (15 kg)	\$ 228.00	\$ 228.00	€ 183.87	£ 148.05
U-2780	9" x 3' Bit	60 lbs (27 kg)	\$ 3,124.00	\$ 3,124.00	€ 2,519.35	£ 2,028.57
U-2781	12" x 3' Bit	83 lbs (38 kg)	\$ 347.00	\$ 347.00	€ 279.84	£ 225.32
U-2782	15" x 3' Bit	98 lbs (44kg)	\$ 457.00	\$ 457.00	€ 368.55	£ 296.75
U-2783	18" x 3' Bit	115 lbs (52 kg)	\$ 502.00	\$ 502.00	€ 404.84	£ 325.97
U-2784	24" x 3' 8 teeth Bit	164 lbs (74 kg)	\$ 549.00	\$ 549.00	€ 442.74	£ 356.49
U-2785	30" x 3' - 9 teeth	166 lbs (75 kg)	\$ 585.00	\$ 585.00	€ 471.77	£ 379.87
U-2910	12" Extension	21 lbs (10 kg)	\$ 146.00	\$ 146.00	€ 117.74	£ 94.81

<b>HYDAULIC QUICK CONNECT COUPLING KIT</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
U-3488	Flat Face couplers (Set of 2)	5 lbs (2 kg)	\$ 175.00	\$ 175.00	€ 141.13	£ 113.64
U-2708	Poppet quick connect couplers (2)	5 lbs (2 kg)	\$ 40.00	\$ 40.00	€ 32.26	£ 25.97

<b>DOZER BLADE</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
U-2771	Dozer Blade 46"	205 lbs (93 kg)	\$ 1,615.00	\$ 1,615.00	€ 1,302.42	£ 1,048.70

<b>BUCKET BROOM</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
TBA	42" Mini Bucket Broom	205lbs (93kg)	\$ 4,226.00	\$ 4,226.00	€ 3,408.06	£ 2,744.16
TBA	Mounting Kit	31 lbs (14kg)	\$ 179.00	\$ 179.00	€ 144.35	£ 116.23
TBA	Wafers Kit/ poly	31 lbs (14kg)	\$ 506.00	\$ 506.00	€ 408.06	£ 328.57

<b>SWEEPER</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
TBA	42 " Manual Angle Mini Sweeper	390 lbs (177 kg)	\$ 4,957.00	\$ 4,957.00	€ 3,997.58	£ 3,218.83
TBA	42" Hyd Angle Mini Sweeper	430 lbs (195 kg)	\$ 6,339.00	\$ 6,339.00	€ 5,112.10	£ 4,116.23
TBA	Caster Wheel Kit	45 lbs (21 kg)	\$ 855.00	\$ 855.00	€ 689.52	£ 555.19
TBA	Poly Brushes	65 lbs (29 kg)	\$ 9.91	\$ 9.91	€ 7.99	£ 6.44
TBA	Mix Brushes	75 lbs (34 kg)	\$ 12.00	\$ 12.00	€ 9.68	£ 7.79

\*North American customers add 8% for freight rates  
All others call for rates

<b>FORKS</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
U-2799	Pallet Fork Framesw/ 32" Tines	162 lbs (73 kg)	\$ 676.00	\$ 676.00	€ 545.16	£ 438.96
U-2772	Pallet Fork Frame w/42" Tines	162 lbs (73 kg)	\$ 678.00	\$ 678.00	€ 546.77	£ 440.26

<b>GRAPPLES</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
TBA	42" Mini Brush Grapple	270 lbs (122 kg)	\$ 2,278.00	\$ 2,278.00	€ 1,837.10	£ 1,479.22
TBA	42" Mini Scrap Grapple	270 lbs (122 kg)	\$ 2,060.00	\$ 2,060.00	€ 1,661.29	£ 1,337.66
TBA	42" Bolt on Cutter bar Assy- optional	22 lbs (10 kg)	\$ 84.00	\$ 84.00	€ 67.74	£ 54.55

<b>LANDSCAPE TOOLS</b>						
Unit #	Description	Shipping Weight	MSRP CDN	MSRP US	MSRP EURO	MSRP GBP
TBA	48" Leveler	135 lbs (61 kg)	\$ 595.00	\$ 595.00	€ 479.84	£ 386.36
TBA	Mini Rock Bucket 42" w 1 1/8" tines	180 lbs (82kg)	\$ 1,061.00	\$ 1,061.00	€ 855.65	£ 688.96
TBA	Mini Rock Bucket 42" w 3/4" tines	116 lbs (53kg)	\$ 1,055.00	\$ 1,055.00	€ 850.81	£ 685.06
TBA	Stump Grinder 8-11GPM	218 lbs (99kg)	\$ 2,181.00	\$ 2,181.00	€ 1,758.87	£ 1,416.23
TBA	Universal Mount for Stump Grinder	67 lbs (30kg)	\$ 399.00	\$ 399.00	€ 321.77	£ 259.09
TBA	Hose Kit	15 lbs (7kg)	\$ 237.00	\$ 237.00	€ 191.13	£ 153.90
TBA	Wheel with bolt on teeth	32 lbs (14kg)	\$ 1,203.00	\$ 1,203.00	€ 970.16	£ 781.17
TBA	Wheel with Square Teeth	36lbs (16kg)	\$ 719.00	\$ 719.00	€ 579.84	£ 466.88
U-2831	Sod Roller	160lbs (73kg)	\$ 2,284.00	\$ 2,284.00	€ 1,841.94	£ 1,483.12
U-2832	40" Hyd Tiller	320lbs (145kg)	\$ 3,820.00	\$ 3,820.00	€ 3,080.65	£ 2,480.52

\*North American customers add 8% for freight rates  
All others call for rates